



Storageflex™ LTO Tape Automation Products

StorageLoader LTO

Drive Type	Capacity	Transfer Rate	Interface	Warranty
1x LTO-4 HH	6.4TB / 12.8TB*	0.3 TB/hr / 0.6 TB/hr*	SCSI, SAS, FC	1-year NBD OSS‡
1x LTO-5 HH	12TB / 24TB*	0.5 TB/hr / 1.0 TB/hr*	SAS, FC	
1x LTO-6 HH	20TB / 50TB*	0.6 TB/hr / 1.4 TB/hr*	SAS	



POSITIONING AND FEATURES

Best value LTO tape automation for SMBs.	Capacity up to 50TB* (compressed).
1U form factor, 8 slots and 1x LTO HH drive.	Performance up to 1.4 TB/hr* (compressed).
Available with LTO-4 HH, LTO-5 HH & LTO-6 HH.	Interface choices: SCSI, SAS and FC connectivity, WORM & AES 256-bit Encryption.
Barcode, remote management and rackmount included.	

StorageLibrary T24

Drive Type	Capacity	Transfer Rate	Interface	Warranty
2x LTO-4 HH	19.2TB / 38.4TB*	0.6 TB/hr / 1.2 TB/hr*	SCSI, SAS, FC	1-year NBD OSS‡
2x LTO-5 HH	36TB / 72TB*	1.0 TB/hr / 2.0 TB/hr*	SAS, FC	
2x LTO-6 HH	60TB / 150TB*	1.2 TB/hr / 2.9 TB/hr*	SAS	



POSITIONING AND FEATURES

Affordable LTO automation for SMBs and small to medium data centers.	Capacity up to 150TB* (compressed).
2U form factor, 12 or 24 slots, 2x HH drives or 1x FH drive.	Performance up to 2.9 TB/hr* (compressed).
Available with LTO-4 HH, LTO-5 HH & LTO-6 HH.	Interface choices: SCSI, SAS and FC connectivity, WORM & AES 256-bit Encryption.
Barcode, remote management and rackmount included.	Field replaceable drives enable customers to upgrade capacity and performance.

StorageLibrary T40+

Drive Type	Capacity	Transfer Rate	Interface	Warranty
4x LTO-4 HH	32TB / 64TB*	1.2 TB/hr / 2.3 TB/hr*	SCSI, SAS,	1-year NBD OSS‡
4x LTO-5 HH	60TB / 120TB*	2.0 TB/hr / 4.0 TB/hr*	SAS, FC	
4x LTO-6 HH	100TB / 250TB*	2.3 TB/hr / 5.8 TB/hr*	SAS	



POSITIONING AND FEATURES

Professional LTO automation for SMBs and small to medium data centers.	Enterprise performance, reliability and features.
Capacity up to 250TB* (compressed).	Redundant power supply, barcode, remote mgmt, rackmount included.
Performance up to 5.8 TB/hr* (compressed).	WORM & AES 256-bit encryption, LTO-4 HH, LTO-5 HH & LTO-6 HH.
4U form factor, 24 or 40 slots, 4x HH drives or 2x FH drives.	Stack up to 5x T40+ units in a 19" rack, 188 slots & 1.2PB.



Storageflex™ LTO Tape Automation Products

StorageLibrary T80+

Drive Type	Capacity	Transfer Rate	Interface	Warranty
8x LTO-5 HH	115.5TB / 231TB*	4.0 TB/hr / 8.0 TB/hr*	SAS, FC	1-year NBD OSS‡
8x LTO-6 HH	192.5TB / 481TB*	4.6 TB/hr / 11.5 TB/hr*	SAS, FC	

POSITIONING AND FEATURES

Professional LTO automation for SMBs and medium to large data centers.

77 slots, 8x HH drives or 4x FH drives, SCSI, SAS and FC connectivity.

8U form factor, Redundant Power, Partitioning, Export/Import slot, barcode.



StorageLibrary T120+

Drive Type	Capacity	Transfer Rate	Interface	Warranty
12x LTO-4 HH	171TB / 342TB*	6.0 TB/hr / 12.0 TB/hr*	SAS, FC	1-year NBD OSS‡
12x LTO-5 HH	285TB / 712.5TB*	6.9 TB/hr / 17.3 TB/hr*	SAS, FC	

POSITIONING AND FEATURES

Professional LTO automation for SMBs and medium to large data centers.

114 slots, 12x HH drives or 6x FH drives, SCSI, SAS and FC connectivity.

12U form factor, Redundant Power, Partitioning, Export/Import slot, barcode.



StorageLibrary T160+

Drive Type	Capacity	Transfer Rate	Interface	Warranty
16x LTO-4 HH	226.5TB / 453TB*	8.0 TB/hr / 16.0 TB/hr*	SAS, FC	1-year NBD OSS‡
16x LTO-5 HH	377.5TB / 943.8TB*	9.2 TB/hr / 23.0 TB/hr*	SAS, FC	

POSITIONING AND FEATURES

Professional LTO automation for SMBs and medium to large data centers.

151 slots, 16x HH drives or 8x FH drives, SCSI, SAS and FC connectivity.

16U form factor, Redundant Power, Partitioning, Export/Import slot, barcode.



StorageLibrary T200+

Drive Type	Capacity	Transfer Rate	Interface	Warranty
20x LTO-4 HH	282TB / 564TB*	9.8 TB/hr / 19.6 TB/hr*	SAS, FC	1-year NBD OSS‡
20x LTO-5 HH	470TB / 1175TB*	11.2 TB/hr / 28.1 TB/hr*	SAS, FC	

POSITIONING AND FEATURES

Professional LTO automation for SMBs and medium to large data centers.

188 slots, 20x HH drives or 10x FH drives, SCSI, SAS and FC connectivity.

20U form factor, Redundant Power, Partitioning, Export/Import slot, barcode.



* Native / Compressed. Assumes a compression ratio of 2:1 on LTO-4/5 & 2.5:1 on LTO-6

‡ Product warranty may be subject to change in some regions. Please contact Storageflex for more information.